

Modelling and Analysis of Wirelessly Interrogated SAW based Micropumps for Drug Delivery Applications

by

Don Wenura Eranda Dissanayake

B. Eng Computer Systems (First Class Honours),
University of Adelaide, 2004

Thesis submitted for the degree of

Doctor of Philosophy

in

School of Electrical and Electronic Engineering,
Faculty of Engineering, Computer and Mathematical Sciences
The University of Adelaide

April 2010

Bibliography

- ADLER-E. L. (2000). Bulk and surface acoustic waves in anisotropic solids, *International Journal of High Speed Electronics and Systems*, **10**(3), pp. 653–684.
- AHMADI-M. M., AND JULLIEN-G. A. (2009). A Wireless-Implantable Microsystem for Continuous Blood Glucose Monitoring, *IEEE Transactions on Biomedical Circuits and Systems*, **3**(3), pp. 169–180.
- ANSYS INCORPORATION. (2009a). ANSYS Help Guide–V.11. <http://www.kxcad.net/ansys/ANSYS/ansyshelp/index.htm> (visited on 12/11/2009).
- ANSYS INCORPORATION. (2009b). ANSYS home page. <http://www.ansys.com/> (visited on 12/11/2009).
- ATEYA-D. A., SHAH-A. A., AND HUA-S. Z. (2004). An electrolytically actuated micropump, *Review of Scientific Instruments*, **75**(4), pp. 915–920.
- BADRAN-M., AND MOUSSA-M. (2004). On the design of an electrohydrodynamic ion drag micropump, *Proc. of the 2004 International Conference on MEMS, NANO and Smart Systems (ICMENS04)*, pp. 137–140.
- BAO-M. H. (2000). Basic mechanics of beams and diaphragm structures. in *Micro mechanical transducers: pressure sensors, accelerometers, and gyroscopes (Hand Book of Sensors and Actuators)*, 8 : 23–87, Elsevier, New York.
- BAROUD-C. N., DELVILLE-J. P., AND WUNENBURGER-R. (2005). Laser-actuated microfluidic building blocks, *Proc. of SPIE-optical trapping and optical micromanipulation II*, **5930**, pp. 1 – 8.
- BENARD-W. L., KAHN-H., HEUER-A. H., AND HUFF-M. A. (1997). Titanium–nickel shape–memory alloy actuated micropump, *Proc. of International Conference on Solid–State Sensors and Actuators*, **1**, pp. 361–364.
- BENARD-W. L., KAHN-H., HEUER-A. H., AND HUFF-M. A. (1998). Thin-film shape–memory alloy actuated micropumps, *Journal of Microelectromechanical Systems*, **7**(2), pp. 245–251.
- BOHM-S., OLTHUIS-W., AND BERGVELD-P. (1999). Plastic micropump constructed with conventional techniques and materials, *Sensors and Actuators, A: Physical*, **77**(3), pp. 223–228.
- BOUROUINA-T., BOSSEBOEUF-A., AND GRANDCHAMP-J. P. (1997). Design and simulation of an electrostatic micropump for drug–delivery applications, *Journal of Micromechanics and Microengineering*, **7**(3), pp. 186–188.
- CABUZ-C., HERB-W. R., CABUZ-E. I., AND LU-S. T. (2001). The dual diaphragm pump, *Proc. of the IEEE Micro Electro Mechanical Systems (MEMS)*, pp. 519–522.
- CAVUOTO-J. (2004). Neural engineering’s image problem, *IEEE Spectrum*, **41**(4), pp. 32–37.
- CHEN-C. H., AND SANTIAGO-J. G. (2002). A planar electroosmotic micropump, *Journal of Microelectromechanical Systems*, **11**(6), pp. 672–683.

Bibliography

- CHEN-L., WANG-H., MA-J., WANG-C., AND GUAN-Y. (2005). Fabrication and characterization of a multi-stage electroosmotic pump for liquid delivery, *Sensors and Actuators, B: Chemical*, **104**(1), pp. 117–123.
- CHEN-X., CUI-D. F., LIU-C. C., AND LI-H. (2008). Microfluidic chip for blood cell separation and collection based on crossflow filtration, *Sensors and Actuators B*, **130**, pp. 216–221.
- CHOI-J. H., AND KIM-D. K. (2009). A Remote Compact Sensor for the Real-Time Monitoring of Human Heartbeat and Respiration Rate, *IEEE Transactions on Biomedical Circuits and Systems*, **3**(3), pp. 181–188.
- ČIPLYS-D., AND RIMEIKA-R. (1999). Measurements of electromechanical coupling coefficient for surface acoustic waves in proton-exchanged lithium niobate, *ULTRAGARSAS journal*, **33**(3), pp. 14–20.
- COLE-M. W., AND FLEMISH-J. R. (1992). Rapid plan view fabrication of semiconductor TEM samples for interface strain and grain size analysis, In: *Proc. of the Materials Research Society Symposium (Specimen Preparation for Transmission Electron Microscopy of Materials-III)*, Vol. 254, pp. 233–238.
- CUI-Q., LIU-C., AND ZHA-X. F. (2007). Study on a piezoelectric micropump for the controlled drug delivery system, *Microfluidics and Nanofluidics*, **3**(4), pp. 377 – 390.
- CUI-Q., LIU-C., AND ZHA-X. F. (2008). Simulation and optimization of a piezoelectric micropump for medical applications, *The International Journal of Advanced Manufacturing Technology*, **36**(5), pp. 516–524.
- DARABI-J., RADA-M., OHADI-M., AND LAWLER-J. (2002). Design, fabrication, and testing of an electrohydrodynamic ion-drag micropump, *Journal of Microelectromechanical Systems*, **11**(6), pp. 684–690.
- DELBRIDGE-A. (2001). *The Macquarie Dictionary*, Third edn, The Macquarie Library, North Ryde, NSW, Australia.
- DEO-S. K., MOSCHOU-E. A., PETEU-S. F., BACHAS-L. G., AND DAUNERT-S. (2003). Responsive drug delivery systems, *Analytical chemistry*, **75**, pp. 206–213.
- DISSANAYAKE-D. W., TIKKA-A. C., AL-SARAWI-S., AND ABBOTT-D. (2007). Radio frequency controlled microvalve for biomedical applications, *Proc. of SPIE-Smart Materials IV*, **6413**, pp. Article 64130D: 1–13.
- DVOESHERSTOV-M. Y., AND CHIRIMANOV-A. P. (1999). Numerical analysis of a surface and leaky surface acoustic wave in new piezoelectric KNbO₃, PKN, and LGN crystals, *Radiophysics and Quantum Electronics*, **42**(5), pp. 431–438.
- DVOESHERSTOV-M. Y., PETROV-S. G., CHEREDNIK-V. I., ., AND CHIRIMANOV-A. P. (2000). Transformation of modes of surface acoustic waves in strong KNbO₃ and PKN piezoelectric crystals, *Radiophysics and Quantum Electronics*, **43**(5), pp. 400–406.
- FENG-G. H., AND KIM-E. S. (2005). Piezoelectrically actuated dome-shaped diaphragm micropump, *Journal of Microelectromechanical Systems*, **14**(2), pp. 192–199.

- FRANÇAIS-O. (2000). Analysis of an electrostatic microactuator with the help of matlab/simulink: transient and frequency characteristics, *Proc. of MSM 2000*, pp. 281–284.
- FUHR-G., HAGEDORN-R., MULLER-T., BENECKE-W., AND WAGNER-B. (1992). Pumping of water solutions in microfabricated electrohydrodynamic systems, *Proc. of IEEE Micro Electro Mechanical Systems*, pp. 25–30.
- FÜLDNER-M., DEHÉ-A., AND LERCH-R. (2005). Analytical Analysis and Finite Element Simulation of Advanced Membranes for Silicon Microphones, *IEEE Sensors Journal*, **5**(5), pp. 857–863.
- GAD-EL-HAK-M. (2002). *The MEMS Handbook*, CRC Press, New York.
- GAMBOA-A. R., MORRIS-C. J., AND FORSTER-F. K. (2005). Improvements in fixed-valve micropump performance through shape optimization of valves, *Journal of Fluids Engineering*, **127**, pp. 339–346.
- GANTNER-A., HOPPE-R. H. W., KÖSTER-D., SIEBERT-K. G., AND WIXFORTH-A. (2007). Numerical simulation of piezoelectrically agitated surface acoustic waves on microfluidic biochips, *Computing and Visualization in Science*, **10**(3), pp. 145–161.
- GARDNER-J. W., VARADAN-V. K., AND AWADELKARIM-O. O. (2001). *Microsensors, MEMS, and Smart Devices*, First edn, Tsinghua University Press, Beijing, chapter : Microsensors, Introduction to SAW devices, Surface acoustic waves in solids, IDT microsensor parameter measurement, IDT microsensor fabrication, IDT microsensors, pp. 227–396.
- GERLACH-T. (1998). Microdiffusers as dynamic passive valves for micropump applications, *Sensors and Actuators A: Physical*, **69**(2), pp. 181–191.
- GILBERT-J. R., ANANTHASURESH-G. K., AND SENTURIA-S. D. (1996). 3D modeling of contact problems and hysteresis in coupled electro-mechanics, *Micro Electro Mechanical Systems*, pp. 127–132.
- GIOVANNI-M. D. (1982). *Flat and Corrugated Diaphragm Design Handbook*, Second edn, Marcel Dekker Inc., New York, chapter : The Design of Corrugated Diaphragms, pp. 247–320.
- GUO-S., AND ASAKA-K. (2003). Polymer-based new type of micropump for bio-medical application, *Proc. of IEEE International Conference on Robotics and Automation*, **2**, pp. 1830–1835.
- GUO-S., FUKUDA-T., AND ASAKA-K. (2003). A new type of fish like underwater microrobot, *Proc. of the IEEE/ASME Transactions on Mechatronics*, pp. 136–141.
- HAMSCH-M. (2004). An interrogation unit for passive wireless SAW sensors based on fourier transform, *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, **51**, pp. 1449–1455.
- HD MICROSYSTEMS. (2008). *PI-2600 LX series, low stress polyimides, Product information and process guidelines*, HD-MicroSystems, Parlin, NJ.
- HORENSTEIN-M. N., PERREAU-L. A., AND BIFANO-T. G. (2000). Differential capacitive position sensor for planar MEMS structures with vertical motion, *Sensors and Actuators*, **80**, pp. 53–61.
- HSU-Y.-C., AND LE-N.-B. (2008). Inertial effects on flow rate spectrum of diffuser micropumps, *Biomed Microdevices*, **10**, pp. 681–692.

Bibliography

- HSU-Y. C., LIN-S. J., AND HOU-C. C. (2008). Development of peristaltic antithrombogenic micropumps for in vitro and ex vivo blood transportation tests, *Microsystem Technologies*, **14**(1), pp. 31–41.
- HUANG-L., WANG-W., MURPHY-M. C., LIAN-K., AND LING-Z.-G. (2000). LIGA fabrication and test of a DC type magnetohydrodynamic (MHD) micropump, *Microsystem Technologies*, **6**(6), pp. 235–240.
- HUEBNER-K. H., THORNTON-E. A., AND BYRON-T. D. (2001). *The Finite Element Method for Engineers*, Fourth edn, Wiley InterScience, New York.
- HU-Y. C., CHANG-C. M., AND HUANG-S. C. (2004). Some design considerations on the electrostatically actuated microstructures, *Sensors and Actuators A*, **112**, pp. 155–161.
- IPPOLITO-S. J., KALANTAR-ZADEH-K., WLODARSKI-W., AND POWELL-D. A. (2002). Finite-element analysis for simulation of layered SAW devices with XY LiNbO₃ substrate, *Proc. of SPIE-Smart Structures, Devices, and Systems*, **4935**, pp. 120–131.
- IVERSON-B. D., AND GARIMELLA-S. V. (2008). Recent advances in microscale pumping technologies: a review and evaluation, *Microfluidics and Nanofluidics*, **5**(2), pp. 145–174.
- IZZO-I., ACCOTO-D., MENCIASSI-A., SCHMITT-L., AND DARIO-P. (2007). Modeling and experimental validation of a piezoelectric micropump with novel no-moving-part valves, *Sensors and Actuators A: Physical*, **133**(1), pp. 128 – 140.
- JANG-J., AND LEE-S. S. (2000). Theoretical and experimental study of MHD (magnetohydrodynamic) micropump, *Sensors and Actuators A: Physical*, **80**(1), pp. 84–89.
- JEONG-O. C., AND YANG-S. S. (2000). Fabrication and test of a thermopneumatic micropump with a corrugated p+ diaphragm, *Sensors and Actuators A: Physical*, **83**(1), pp. 249–255.
- JEONG-O. C., PARK-S. W., YANG-S. S., AND PAK-J. J. (2005). Fabrication of a peristaltic PDMS micropump, *Sensors and Actuators A: Physical*, **123–124**, pp. 453–458.
- JIANG-X. N., ZHOU-Z. Y., HUANG-X. Y., LI-Y., YANG-Y., AND LIU-C. Y. (1998). Micronozzle/diffuser flow and its application in micro valveless pumps, *Sensors and Actuators A: Physical*, **70**(1–2), pp. 81–87.
- JIN-X., LADABAUM-I., AND KHURI-YAKUB-B. (1998). The microfabrication of capacitive ultrasonic transducers, *Journal of Microelectromechanical Systems*, **7**(3), pp. 295–302.
- JIN-X., LADABAUM-I., DEGERTEKIN-F. L., CALMES-S., AND KHURI-YAKUB-B. T. (1999). Fabrication and characterization of surface micromachined capacitive ultrasonic immersion transducers, *Journal of Microelectromechanical Systems*, **8**, pp. 100–114.
- JOHANSSON-A. J. (2004). *Wireless Communication with Medical Implants: Antennas and Propagation*, PhD thesis, Department of Electroscience, Faculty of Engineering, Lund University, Sweden.
- JONES-I., RICCIARDI-L., HALL-L., HANSEN-H., VARADAN-V., BERTRAM-C., MADDOCKS-S., ENDERLING-S., SAINT-D., AL-SARAWI-S., AND ABBOTT-D. (2008). Wireless RF communication in biomedical applications, *Smart Materials and Structures*, **17**, pp. 015050: 1–10.

- JONG-W. R., KUO-T. H., HO-S. W., CHIU-H. H., AND PENG-S. H. (2007). Flows in rectangular microchannels driven by capillary force and gravity, *International Communications in Heat and Mass Transfer*, **34**(2), pp. 186–196.
- JUDY-J. W., TAMAGAWA-T., AND POLLA-D. L. (1991). Surface micromachined micropump, *Proc. MEMS*, **91**, pp. 182–186.
- JUNG-K. Y., AND KWAK-H. K. (2007). Fabrication and testing of bubble powered micropumps using embedded microheater, *Microfluidics and Nanofluidics*, **3**(2), pp. 161–169.
- JUNWU-K., ZHIGANG-Y., TAIJIANG-P., GUANGMING-C., AND BODA-W. (2005). Design and test of a high-performance piezoelectric micropump for drug delivery, *Sensors and Actuators, A: Physical*, **121**(1), pp. 156–161.
- KABATA-A., AND SUZUKI-H. (2005). Microsystem for injection of insulin and monitoring of glucose concentration, *Proc. of the International conference on Sensors*, pp. 171–174.
- KANNAN-T. (2006). *Finite element analysis of surface acoustic wave resonators*, Master's thesis, University of Saskatchewan.
- KAZARYAN-A. A. (2000). Thin-film capacitive pressure transducers which operate during the deformation of products, *Measurement Techniques*, **43**, No.1, pp. 38–43.
- KE-F., MIAO-J., AND WANG-Z. (2009). A wafer-scale encapsulated RF MEMS switch with a stress-reduced corrugated diaphragm, *Sensors and Actuators A: Physical*, **151**(2), pp. 237–243.
- KIM-J. H., NA-K. H., KANG-C. J., AND KIMA-Y. S. (2005). A disposable thermopneumatic-actuated micropump stacked with PDMS layers and ITO-coated glass, *Sensors and Actuators, A: Physical*, **120**(2), pp. 365–369.
- KOCH-M., HARRIS-N., EVANS-A. G. R., WHITE-N. M., AND BRUNNSCHWEILER-A. (1998). A novel micromachined pump based on thick-film piezoelectric actuation, *Sensors and Actuators, A: Physical*, **70**(1–2), pp. 98–103.
- KUROSAWA-M., WATANABE-T., AND HIGUCHI-T. (1995). Surface acoustic wave atomizer with pumping effect, *IEEE 8th Int. Workshop on MEMS (MEMS'95)*, pp. 25–30.
- LAKSHMINARAYANA-H. (2004). *Finite Elements Analysis and Procedures in Engineering*, Orient Black-swan.
- LEE-B., AND KIM-E. (2000). Analysis of partly-corrugated rectangular diaphragms using the Rayleigh-Ritz method, *Journal of Microelectromechanical Systems*, **9**(3), pp. 399–406.
- LEE-S., AND KIM-K. J. (2006). Design of IPMC actuator-driven valve-less micropump and its flow rate estimation at low Reynolds numbers, *Smart Materials and Structures*, **15**(4), pp. 1103–1109.
- LEUNG-Y. S. K., MAILLER-D., REY-MERMET-G., MONKEWITZ-P. A., RENAUD-P., AND VAN LINTEL-H. T. G. (1998). Microfluidics of a planar microfabricated fluid filter, *American Society of Mechanical Engineers, Dynamic Systems and Control Division*, **66**, pp. 165–170.
- LIFESPAN. (2009). Lifespan. <http://www.lifespan.org/> (visited on 01/11/2009).

Bibliography

- LINNEMANN-R., WOIAS-C., SENFFT-J. A., LINNEMANN-R., AND DITTERICH-J. A. (1998). Self-priming and bubble-tolerant piezoelectric silicon micropump for liquids and gases, *Proc. of the IEEE Micro Electro Mechanical Systems (MEMS)*, pp. 532–537.
- LI-Y., SHAWGO-R. S., TYLER-B., HENDERSON-P. T., VOGEL-J. S., ROSENBERG-A., STORM-P. B., LANGER-R., BREM-H., AND CIMA-M. J. (2004). In vivo release from a drug delivery MEMS device, *Journal of Controlled Release*, **100**(2), pp. 211–219.
- LÖHNER-R. (2008). *Applied CFD Techniques*, Second edn, John Wiley and Sons Ltd. West Sussex, England, chapter : Introduction and general considerations, pp. 1–6.
- LOVERICH-J., KANNO-I., AND KOTERA-H. (2007). Single-step replicable microfluidic check valve for rectifying and sensing low Reynolds number flow, *Microfluidics Nanofluidics*, **3**(4), pp. 427 – 435.
- LUGINBUHL-P., COLLINS-S. D., RACINE-G. A., GRETILLAT-M. A., DE ROOIJ-N. . F., BROOKS-K. G., AND SETTER-N. (1997). Microfabricated lamb wave device based on PZT sol-gel thin film for mechanical transport of solid particles and liquids, *Journal of Microelectromechanical Systems*, **6**(4), pp. 337–346.
- MA-B., SHENG-L., GAN-Z., LIU-G., CAI-X., ZHANG-H., AND YANG-Z. (2006). A PZT insulin pump integrated with a silicon micro needle array for transdermal drug delivery, *Proc. of Electronic Components and Technology Conference*, **2006**, pp. 677–681.
- MACHAUF-A., NEMIROVSKY-Y., AND DINNAR-U. (2005). A membrane micropump electrostatically actuated across the working fluid, *Journal of Micromechanics and Microengineering*, **15**(12), pp. 2309–2316.
- MAILLEFER-D. (2003). Development of novel drug delivery products based on micro system technologies, *International Conference and Exhibition on Micro Electro, Opto, Mechanical Systems and Components*, pp. 387–394.
- MATSUMOTO-S., MAEDA-R., AND KLEIN-A. (1999). Characterization of a valveless micropump based on liquid viscosity, *Microscale Thermophysical Engineering*, **3**(1), pp. 31 – 42.
- MAUGIN-G. A. (1985). *Nonlinear electromechanical effects and applications*, First edn, World Sceintific Publishing Co. Pte. Ltd., chapter : Rayleigh Surface Waves, pp. 104–142.
- MEDTRONIC INCORPORATION. (2009). Medtronic home page. <http://www.medtronic.com/> (visited on 24/11/2009).
- MEMS AND NANOTECHNOLOGY CLEARINGHOUSE. (2009). MEMSnet Material. <http://www.memsnet.org/material/> (visited on 12/11/2009).
- MENG-A. H., NGUYEN-N. T., AND WHITE-R. M. (2000). Focused flow micropump using ultrasonic flexural plate waves, *Biomedical Microdevices*, **2**(3), pp. 169–174.
- MILSTEIN-L. B., AND DAS-P. (1979). Surface Acoustic Wave Devices, *IEEE Communications Magazine*, **17**, pp. 25–33.
- MIYAZAKI-S., KAWAI-T., AND ARARAGI-M. (1991). A piezo-electric pump driven by a flexural progressive wave, *IEEE 4th Int. Workshop on MEMS (MEMS'91)*, pp. 283–288.

- MORONEY-R. M., WHITE-R. M., AND HOWE-R. T. (1991a). Microtransport induced by ultrasonic Lamb waves, *Applied Physics Letters*, **59**(7), pp. 774–776.
- MORONEY-R. M., WHITE-R. M., AND HOWE-R. T. (1991b). Ultrasonically induced microtransport, *IEEE 4th Int. Workshop on MEMS (MEMS'91)*, pp. 277–282.
- MORRIS-C. J., AND FORSTER-F. K. (2000). Optimization of a circular piezoelectric bimorph for a micropump driver, *Journal of Micromechanics and Microengineering*, **10**(3), pp. 459–465.
- NGA-T. Y., JIANGB-T. Y., LIB-H., LAMB-K. Y., AND REDDYC-J. N. (2004). A coupled field study on the non-linear dynamic characteristics of an electrostatic micropump, *Journal of Sound and Vibration*, **273**(4–5), pp. 989–1006.
- NGUYEN-N. T., HUANG-X., AND CHUAN-T. K. (2002). MEMS-Micropumps: A review, *Transactions of the ASME Journal of Fluids Engineering*, **124**, pp. 384–392.
- NGUYEN-N. T., MENG-A. H., BLACK-J., AND WHITE-R. M. (2000a). Integrated flow sensor for in situ measurement and control of acoustic streaming in flexural plate wave micropumps, *Sensors and Actuators, A: Physical*, **79**(2), pp. 115–121.
- NGUYEN-N.-T., MENG-A. H., BLACK-J., AND WHITE-R. M. (2000b). Integrated flow sensor for in situ measurement and control of acoustic streaming in flexural plate wave micropumps, *Sensors and Actuators A: Physical*, **79**(2), pp. 115–121.
- NISAR-A., AFZULPURKAR-N., MAHAISAVARIYA-B., AND TUANTRANONT-A. (2008a). MEMS-based micropumps in drug delivery and biomedical applications, *Sensors and Actuators B: Chemical*, **130**(2), pp. 917 – 942.
- NISAR-A., AFZULPURKAR-N., MAHAISAVARIYA-B., AND TUANTRANONT-A. (2008b). Multifield analysis of a piezoelectrically actuated valveless micropump, *Sensors and Transducers Journal*, **94**(7), pp. 176–195.
- NISAR-A., AFZULPURKAR-N., MAHAISAVARIYA-B., AND TUANTRANONT-A. (2008c). Multifield analysis using multiple code coupling of a MEMS based micropump with biocompatible membrane materials for biomedical applications, *International Conference on BioMedical Engineering and Informatics*, **1**, pp. 531–535.
- NISAR-A., AFZULPURKAR-N., TUANTRANONT-A., AND MAHAISAVARIYA-B. (2008d). Three Dimensional Transient Multifield Analysis of a Piezoelectric Micropump for Drug Delivery System for Treatment of Hemodynamic Dysfunctions, *Cardiovascular Engineering*, **8**, pp. 203–218.
- OH-W. K., AND CHONG-H. A. (2006). A review of microvalves, *Journal of Micromechanics and Microengineering*, **16**(5), pp. R13–R39.
- OLSSON-A. (1998). *Valve-less Diffuser Micropumps*, PhD thesis, Instrumentation Laboratory, Department of Signals, Sensors and Systems, Royal Institute of Technology, Sweden.
- OLSSON-A., STEMME-G., AND STEMME-E. (1996). Diffuser-element design investigation for valve-less pumps, *Sensors and Actuators A: Physical*, **57**(2), pp. 137–143.
- OLSSON-A., STEMME-G., AND STEMME-E. (2000). Numerical and experimental studies of flat-walled diffuser elements for valve-less micropumps, *Sensors and Actuators, A*, **84**(1–2), pp. 165–175.

Bibliography

- PANG-J., ZOU-Q., TAN-Z., QIAN-X., LIU-L., AND LI-Z. (1998). Study of single-chip integrated microfluidic system, *Proc. of International Conference on Solid-State and Integrated Circuit Technology*, pp. 895–898.
- PAN-T., McDONALD-S. J., KAI-E. M., AND ZIAIE-B. (2005a). A magnetically driven PDMS micropump with ball check-valves, *Journal of Micromechanics and Microengineering*, **15**(5), pp. 1021–1026.
- PAN-T., McDONALD-S. J., KAI-E. M., AND ZIAIE-B. (2005b). A magnetically driven PDMS micropump with ball check-valves, *Journal of Microelectromechanical Systems*, **15**(5), pp. 1021 – 1026.
- PITZ-I., HALL-L. T., HANSEN-H. J., VARADAN-V. K., BERTRAM-C. D., MADDOCKS-S., ENDERLING-S., SAINT-D., AL-SARAWI-S. F., AND ABBOTT-D. (2002). Trade-offs for wireless transcutaneous RF communication in biotelemetric applications, *Proc. of SPIE–Biomedical Applications of Micro- and Nanoengineering*, **4937**, pp. 307–318.
- PRESCOTT-J. H., LIPKA-S., BALDWIN-S., SHEPPARD-J., MALONEY-J. M., COPPETA-J., YOMTOV-B., STAPLES-M. A., AND SANTINI-J. (2006). Chronic, programmed polypeptide delivery from an implanted, multireservoir microchip device, *Nature Biotechnology*, **24**, pp. 437–438.
- RANADEV-V. V., AND HOLLINGER-M. A. (2004). *Drug Delivery Systems*, Second edn, CRC Press LLC, Florida, USA, chapter : Implants in Drug Delivery, pp. 115–149.
- RANGAN-C. S., SARMA-G. R., AND MANI-V. S. V. (1983). *Instrumentation Devices and Systems*, Second edn, Tata McGraw-Hill Pub. Comp. Ltd., New Delhi, chapter : Vibration, pp. 82–112.
- RAZZACKI-S. Z., THWAR-P. K., YANG-M., UGAZ-V. M., AND BURNS-M. A. (2004). Integrated microsystems for controlled drug delivery, *Advanced Drug Delivery Reviews*, **56**(2), pp. 185–198.
- RICHTER-A., AND SANDMAIER-H. (1990). An electrohydrodynamic micropump, *Proc. of IEEE Micro Electro Mechanical Systems–An Investigation of Micro Structures, Sensors, Actuators, Machines*, pp. 99–104.
- ROSA-S., AND PINHO-F. T. (2006). Pressure drop coefficient of laminar Newtonian flow in axisymmetric diffusers, *International Journal of Heat and Fluid Flow*, **27**, pp. 319–328.
- ROUSCHE-P. J., PELLINEN-D. S., PIVIN-D. P., JR-J. C. W., VETTER-R. J., AND KIPKE-D. R. (2001). Flexible polyimide-based intracortical electrode arrays with bioactive capability, *IEEE transactions on bio-medical engineering*, **48**(3), pp. 361–371.
- RUPPEL-C. C. W., REINDL-L., AND WEIGEL-R. (2002). SAW devices and their wireless communication applications, *IEEE Microwave Magazine*, ISSN 1527-3342, **3**(2), pp. 65–71.
- SAMEL-B., GRISS-P., AND STEMME-G. (2007). A thermally responsive PDMS composite and its microfluidic applications, *Journal of Microelectromechanical Systems*, **16**(1), pp. 50 – 57.
- SCHMIDT-F., SCZESNY-O., RUPPEL-C., AND MAGORI-V. (1996). Wireless interrogator system for SAW-identification-marks and SAW-sensor components, *Proc. of the 50th IEEE International Symposium on Frequency Control*, pp. 208–215.
- SCHOMBURG-W. K., VOLLMER-J., BUSTGENS-B., FAHRENBERG-J., HEIN-H., AND MENZ-W. (1994). Microfluidic components in LIGA technique, *Journal of Micromechanics and Microengineering*, **4**(4), pp. 186–191.

- SHUXIANG-G., AND FUKUDA-T. (2004). SMA actuator based novel type of micropump for biomedical application, *Proc. of IEEE International Conference on Robotics and Automation*, pp. 1616–1621.
- SINGHAL-V., GARIMELLA-S. V., AND MURTHY-J. Y. (2004). Low Reynolds number flow through nozzle–diffuser elements in valveless micropumps, *Sensors and Actuators A*, **113**, pp. 226–235.
- SKINNER-J. L., CARDINALE-G. F., TALIN-A. A., AND BROCATO-R. W. (2006). Effect of critical dimension variation on SAW correlator energy, *IEEE Transactions on Ultrasonics, Ferroelectrics and Frequency Control*, **53**(2), pp. 497–501.
- SMITS-J. G. (1990). Piezoelectric micropump with three valves working peristaltically, *Sensors and Actuators: A. Physical*, **21**(1–3), pp. 203–206.
- SOIN-N., AND MAJLIS-B. Y. (2006). Development of perfect silicon corrugated diaphragm using anisotropic etching, *Microelectronic Engineering*, **83**, pp. 1438–1441.
- SQUIRES-T., AND QUAKE-S. (2005). Microfluidics: Fluid physics at the nanoliter scale, *Reviews of Modern Physics*.
- STEMME-E., AND STEMME-G. (1993). A valveless diffuser/nozzle–based fluid pump, *Sensors and Actuators: A. Physical*, **39**(2), pp. 159–167.
- STROBL-C. J., GUTTENBERG-Z. V., AND WIXFORTH-A. (2004). A Nano–and pico–dispensing of fluids on planar substrates using SAW, *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control*, **51**(11), pp. 1432–1436.
- STRUCTURE PROBE INC.. (2009). SPI home page. <http://www.2spi.com/> (visited on 10/11/2009).
- SUBRAMANIAN-H., VARADAN-V. K., VARADAN-V. V., AND VELLEKOOPZ-M. J. (1997). Design and fabrication of wireless remotely readable MEMS based microaccelerometers, *Smart Materials and Structures*, **6**(6), pp. 730–738.
- SU-Y. C., AND LIN-L. (2004). A water–powered micro drug delivery system, *Journal of Microelectromechanical Systems*, **13**(1), pp. 75–82.
- SU-Y. C., LIN-L., AND PISANO-A. P. (2002). A water–powered osmotic microactuator, *Journal of Microelectromechanical Systems*, **11**(6), pp. 736–742.
- SUZUKI-H., AND YONEYAMA-R. (2002). A reversible electrochemical nanosyringe pump and some considerations to realize low–power consumption, *Sensors and Actuators, B: Chemical*, **86**(2–3), pp. 242–250.
- SUZUKI-T., TERAMURA-Y., HATA-H., INOKUMA-K., KANNO-I., IWATA-H., AND KOTERA-H. (2007). Development of a micro biochip integrated traveling wave micropumps and surface plasmon resonance imaging sensors, *Microsystem Technologies*, **13**(8–10), pp. 1391–1396.
- TAKEMORI-Y., HORIIKE-S., NISHIMOTO-T., NAKANISHI-H., AND YOSHIDA-T. (2005). High pressure electroosmotic pump packed with uniform silica nanospheres, *Proc. of the International Conference on Solid State Sensors, Actuators and Microsystems*, pp. 1573–1576.
- TESLA-N. (1920). Valvular conduit. U.S. Patent No. 1,329,559.

Bibliography

- TEYMOORI-M. M., AND ABBASPOUR-SANI-E. (2004). Design and simulation of a novel electrostatic peristaltic micromachined pump for drug delivery applications, *Sensors and Actuators, A: Physical*, **117**(2), pp. 222–229.
- TIKKA-A. C., AL-SARAWI-S., AND ABBOTT-D. (2007). Finite element modelling of SAW correlator, *Proc. of SPIE BioMEMS and Nanotechnology III conference*, Vol. 6799, pp. Article 679915: 1–9.
- TIKKA-A. C., AL-SARAWI-S., AND ABBOTT-D. (2008). A remotely interrogatable passive microactuator using SAW correlation, *3rd International Conference on Sensing Technology*, pp. 46–51.
- TSAI-J. H., AND LIN-L. (2001). A thermal bubble actuated micro nozzle-diffuser pump, *Proc. of the IEEE Micro Electro Mechanical Systems (MEMS)*, pp. 409–412.
- TSAI-N. C., AND SUE-C. Y. (2007). Review of MEMS-based drug delivery and dosing systems, *Sensors and Actuators A*, **134**, pp. 555–564.
- TSUI-Y., AND LU-S. (2008). Evaluation of the performance of a valveless micropump by CFD and lumped-system analyses, *Sensors and Actuators*, **148**(1), pp. 138–148.
- UPADHYAY-S. K. (2004). *Seismic Reflection Processing: With Special Reference to Anisotropy*, First edn, Springer–Verlag, Berlin, chapter : Anisotropy Models of Sedimentary Sections and Characteristics of Wave Propagation, pp. 143–201.
- VAN LINTEL-H. T. G., VAN DE POL-F. C. M., AND BOUWSTRA-S. (1988). A piezoelectric micropump based on micromachining of silicon, *Sensors and Actuators*, **15**(2), pp. 153–167.
- VARADAN-V. K., AND VARADAN-V. V. (2000). Microsensors, micromechanical systems (MEMS), and electronics for smart structures and systems, *Smart Materials and Structures*, **9**, pp. 953–972.
- WANG-W., AND SOPER-S. A. (2007). *Bio-MEMS Technologies and Applications*, CRC Press, New York.
- WANG-W. J., LIN-R. M., REN-Y., AND LI-X. X. (2003). Performance of a novel non-planer diaphragm for high-sensitivity structures, *Microelectronics Journal*, **34**(9), pp. 791–796.
- WANG-Y. C., HSU-J. C., KUO-P. C., AND LEE-Y. C. (2008). Loss characteristics and flow rectification property of diffuser valves for micropump applications, *International Journal of Heat and Mass Transfer*, **52**, pp. 328–336.
- WANG-Y. G., SHI-J. L., AND WANG-X. Z. (2009). Large amplitude vibration of heated corrugated circular plates with shallow sinusoidal corrugations, *Applied Mathematical Modelling*, **33**(9), pp. 3523–3532.
- WASHIZU-K. (1975). *Variational methods in elasticity and plasticity*, Second edn, Pergamon Press Ltd., Oxford, chapter : Beams, Plates, pp. 132–182.
- WEIR-R. F., TROYK-P. R., DEMICHELE-G., AND KUIKEN-T. (2003). Implantable myoelectric sensors (IMES) for upper-extremity prosthesis control, *Proc. of the 25th Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, pp. 1562–1565.
- WHITE-F. M. (1999). *Fluid Mechanics*, Fourth edn, McGraw-Hill, New York, chapter : Viscous Flow in Ducts, pp. 325–424.

- WIXFORTH-A. (2003). Acoustically driven planar microfluidics, *Superlattices and Microstructures*, **6**, pp. 389–396.
- WOIAS-P. (2001). Micropumps: summarizing the first two decades, *Proc. of SPIE-Microfluidics and BioMEMS*, **7268**, pp. 39–52.
- WOIAS-P. (2005). Micropumps—Past, progress and future prospects, *Sensors and Actuators, B: Chemical*, **105**(1), pp. 28–38.
- WOLFRAM MATHWORLD. (2009). Euler angles. <http://mathworld.wolfram.com/EulerAngles.html> (visited on 17/08/2009).
- XU-D., WANG-L., DING-G., ZHOU-Y., YU-A., AND CAI-B. (2001). Characteristics and fabrication of NiTi/Si diaphragm micropump, *Sensors and Actuators, A: Physical*, **93**(1), pp. 87–92.
- YAMAHATA-C., LACHARME-F., BURRI-Y., AND GIJS-M. A. M. (2005a). A ball valve micropump in glass fabricated by powder blasting, *Sensors and Actuators B: Chemical*, **110**(1), pp. 1 – 7.
- YAMAHATA-C., LOTTO-C., AL-ASSAF-E., AND GIJS-M. A. M. (2005b). A PMMA valveless micropump using electromagnetic actuation, *Microfluidics and Nanofluidics*, **1**(3), pp. 197–207.
- YANG-Y., ZHOU-Z., YE-X., AND JIANG-X. (1996). Bimetallic Thermally Actuated Micropump, *American Society of Mechanical Engineers, Dynamic Systems and Control Division*, **59**, pp. 351–354.
- YAO-B., LUO-G., FENG-X., WANG-W., CHEN-L., AND WANG-Y. (2004). A microfluidic device based on gravity and electric force driving for flow cytometry and fluorescence activated cell sorting, *Lab on a Chip*, **4**, pp. 603–607.
- YAO-B., PETROVA-R. V., VANFLEET-R. R., AND COFFEY-K. R. (2006). A modified back-etch method for preparation of plan-view high-resolution transmission electron microscopy samples, *J Electron Microsc (Tokyo)*, **55**(4), pp. 209–214.
- YAO-Q., XU-D., PAN-L. S., TEO-A. L. M., HO-W. M., LEE-V. S. P., AND SHABBIR-M. (2007). CFD simulations of flows in valveless micropumps, *Engineering Applications of Computational Fluid Mechanics*, **1**(3), pp. 181–188.
- YOSHIMI-Y., SHINODA-K., MISHIMA-M., NAKAO-K., AND MUNEKANE-K. (2004). Development of an artificial synapse using an electrochemical micropump, *Journal of Artificial Organs*, **7**(4), pp. 210–215.
- YUN-K. S., CHO-I. J., BU-J. U., KIM-C. J., AND YOON-E. (2002). A surface-tension driven micropump for low-voltage and low-power operations, *Journal of Microelectromechanical Systems*, **11**(5), pp. 454–461.
- ZAGLMAYR-S., SCH'BERL-J., AND LANGER-U. (2005). *Progress in Industrial Mathematics at ECMI 2004*, Vol. 8 of *Mathematics in Industry*, Springer–Verlag, Berlin, chapter : Eigenvalue Problems in Surface Acoustic Wave Filter Simulations, pp. 75–99.
- ZAHN-J. D., DESHMUKH-A., PISANO-A. P., AND LIEPMANN-D. (2004). Continuous on-chip micropumping for microneedle enhanced drug delivery, *Biomedical Microdevices*, **6**(3), pp. 183–190.

-
- ZDEBLICK-M. J., AND ANGELL-J. B. (1987). A microminiature electric-to-fluidic valve, *Proc. of International Conference on Solid-State Sensors and Actuators*, pp. 827–829.
- ZENGERLE-R., RICHTER-A., AND SANDMAIER-H. (1992). A micro membrane pump with electrostatic actuation, *Proc. of the IEEE Micro Electro Mechanical Systems (MEMS)*, pp. 19–24.
- ZENGERLE-R., ULRICH-J., KLUGE-S., RICHTER-M., AND RICHTER-A. (1995). A bidirectional silicon micropump, *Sensors and Actuators: A. Physical*, **50**(1–2), pp. 81–86.
- ZENG-S., CHEN-C. H., MIKKELSEN-J. C., AND SANTIAGO-J. G. (2001). Fabrication and characterization of electroosmotic micropumps, *Sensors and Actuators, B: Chemical*, **79**(2–3), pp. 107–114.
- ZHAN-C., LO-T., AND LIU-L. (1996). A silicon membrane micropump with integrated bimetallic actuator, *Chinese Journal of Electronics*, **5**(2), pp. 33–35.
- ZHOU-W., AND LI-W. J. (2004). Micro ICPF actuators for aqueous sensing and manipulation, *Sensors and Actuators A: Physical*, **114**(2–3), pp. 406 – 412.
- ZIAIE-B., BALDI-A., LEI-M., GU-Y., AND SIEGEL-R. A. (2004). Hard and soft micromachining for BioMEMS: Review of techniques and examples of applications in microfluidics and drug delivery, *Advanced Drug Delivery Reviews*, **56**(2), pp. 145–172.
- ZIMMERMANN-S., FRANK-J. A., LIEPMANN-D., AND PISANO-A. P. (2004). A planar micropump utilizing thermopneumatic actuation and in-plane flap valves, *Proc. of the IEEE International Conference on Micro Electro Mechanical Systems (MEMS)*, pp. 462–465.
- ZOU-J. X., YE-Y. Z., ZHOU-Y., AND YANG-Y. (1997). A novel thermally-actuated silicon micropump, *Proc. of International Symposium on Micromechatronics and Human Science*, pp. 231–234.

Index

- accelerometer, 41, 51
- actuator
 - electrostatic, 50
- actuators, 50
- air-structure interface, 147
- Altium Designer, 111
- ANSYS, 9, 127, 175
 - CFX, 9, 137
 - MFS, 75
 - MFX, 75, 138
 - Multi-field solver, 75
- anti-hypertensive drugs, 47
- axial velocity, 119
- batteryless, 174
- bending stiffness, 95, 141
- biomedical applications, 35
 - μ TAS, 138
 - contraception, 46
 - DNA sequencing, 46
 - drug delivery, 13, 18, 27, 128
 - flow cytometry, 46
 - insulin delivery, 16, 20
 - intracavity intervention, 23
 - LoC, 46
 - micromixing, 46
 - nano syringe pump, 29
- boundary condition analysis, 66
 - electrical, 67, 105
 - mechanical, 67, 104
- CFX, 9
- computational fluid dynamics (CFD), 5, 6, 172
- computer aided design, 4
- computer aided modelling, 4
- convergence
 - force, 150
 - microdiaphragm analysis, 99
 - micropump, 149
- corrugation
 - height, 91
 - thickness, 91
 - wavelength, 91
- coupling interfaces, 138
- Decaying constant, 57
- density
 - fluid, 119, 142
 - microdiaphragm, 141
 - SAW substrate, 56
- diffuser, 11, 23, 32, 37, 39, 116, 118
 - area ratio, 124
 - diffuser angle, 118
 - diffuser length, 118
 - flat-walled, 118
 - flow rate, 120
 - neck width, 118
 - total pressure loss coefficient, 120
- diffuser efficiency, 11, 122
- direct coupled solver, 150
- displacement coefficient
 - actuator, 73
 - microdiaphragm, 95
- double Laplacian operator, 141
- drug delivery systems, 2, 14, 27, 34, 35
 - hypertension, 46
 - insulin delivery, 16, 20
- effective plate area, 70
- eigenvalue problem
 - boundary conditions, 69
 - plane wave equations, 60, 61
- electric field intensity, 56
- electric flux density, 56
- electric potential, 56, 62, 93
 - correlated positive signal, 64
 - IDT gap, 65
 - Laplace potential, 67

Index

- negative finger, 65
- positive finger, 64, 65
- propagating SAW, 66
- electromechanical coupling, 60
- electrostatic actuation, 8
- electrostatic force
 - microdiaphragm, 93
 - negative IDT finger, 71
 - per wavelength, 72
 - positive IDT finger, 71
 - total, 72
- element type
 - SOLID122, 76, 98
 - SOLID226, 148
 - SOLID95, 75, 98
- energy
 - actuator, 72
 - microdiaphragm, 95
- fabrication
 - microdiaphragm, 109
 - PCB, 110
 - photolithography, 50
 - sputtering, 111
 - X-ray lithography, 50
- FEA, 172
- finite element analysis (FEA)
 - actuator, 75
 - microdiaphragm, 97
 - micropump, 137
- finite element analysis (FEA), diffuser, 127
- flexural plate wave, 82
- flow rate, 166
 - average, 165
 - diffuser, 122
 - nozzle, 122
- flow rectification, 115, 136
- flow rectification efficiency, 122, 123
- fluid density, 119, 142
- fluid velocity vector, 142
- fluid–structure interaction (FSI), 6, 10
- fluidstructure interaction (FSI), 137
- fluidstructure interface, 147
- gyroscope, 41, 51
- hormone receptors, 46
- hydrostatic pressure, 119
- hydrostatic pressures
 - chamber, 121
 - inlet/outlet, 121
- IDT finger width, 64
- implants, 2, 42, 172
- input voltage, 74
- instantaneous microdiaphragm deflection, 92
- instantaneous plate deflection, 70
- inter digital transducers (IDT), 33, 40
 - divisions per gap, 71
 - electric potential, 62
 - IDT finger length, 71
 - IDT finger width, 71
- Ionic conductive polymer film, 24
- kinetic–energy correction factor, 119
- Lab-on-a-Chip, 14, 15
- lamina flow, 40
- Laplace equation
 - Laplace coefficient, 67
- linear coefficients
 - plane waves, 57
- material properties, 148
- materials
 - 128-YX-LiNbO₃, 60
 - Aluminium, 52, 104
 - copper, 110
 - gold, 52, 104
 - Lead Potassium Niobate, 53
 - Lead Zirconate Titanate, 19
 - Lithium Tantalate, 53
 - Nafion, 24
 - Nikel, 22
 - PI-2610, 104
 - Platinum, 52
 - polyaniline, 24
 - polydimethylsiloxane, 35

- polyimide, 104
- polymethylmethacrylate, 35
- polypyrrole, 24
- Potassium Niobate, 53
- silicon, 18, 52
- Silicon Nitride, 52, 103
- Titanium, 22
- Zinc Oxide, 19
- mechanical displacement, 56
- mechanical stress, 56
- membrane, 16
- MEMS, 50, 138
 - Bio-MEMS, 3
 - Bio-MEMS, 5, 14, 42, 104, 172
 - RF-MEMS, 4, 5, 172
 - Rf-MEMS, 42
- mesh generation
 - actuator, 76
 - microdiaphragm, 99
- micro electro mechanical systems (MEMS), 3, 4
- microdiaphragm, 16, 86, 147
 - corrugation parameters, 91
 - corrugations, 90, 106
 - fabrication, 109
 - stress distribution, 108
 - wavelength, 107
- microdiaphragm characteristics, 89
- microfluidics, 6, 127
- micromixing, 176
- micromotor, 50
- micropump, 3, 7, 15, 16, 50, 172
 - bimetallic, 23
 - bubble-type, 32
 - electrochemical, 29
 - Electrohydrodynamic, 27
 - electromagnetic, 20
 - electroosmotic, 28
 - electroststic, 16
 - electrowetting, 31
 - flexural planar wave, 33
 - magnetohydrodynamic, 26
 - mechanical, 16
- non-mechanical, 25
- osmotic-type, 29
- peristaltic, 15
- piezoelectric, 19
- Shape memory alloy, 22
- thermo-pneumatic, 21
- valveless, 116
- micropump model, 117, 154
- microvalve, 37, 50, 172
 - diffuser/nozzle, 11, 23, 32, 37, 39
 - diffuser/Tesla valve, 39, 40
 - dynamic, 37
 - static, 38, 116
- miocrpump
 - non-mechanical, 16
- modulus of elasticity, 73
- moment of inertia
 - actuator, 73
- multi-field, 5, 10
- multi-field, 165
 - solver, 149
- multifield
 - analysis, 137, 176
- nozzle, 11, 32, 37, 39, 118
 - total pressure loss coefficient, 120
- number of corrugation wavelengths, 91
- numerical analysis
 - boundary element method (BEM), 6
 - computational fluid dynamics (CFD), 6, 127, 137
 - FEA based CFD, 165
 - finite difference method (FDM), 6
 - finite element analysis (FEA), 5, 127
 - finite element method (FEM), 6
- permittivity, 56
- permittivity of air, 68
- phase velocity, 57
- piezoelectric, 16, 40
 - micropump, 19
- piezoelectric analysis, 55
- piezoelectric coupling tensor, 56

Index

- piezoelectric effect, 88
- Poisson ratio, 95
- positive square wave, 64
- pressure recovery coefficient, 123
- radio frequency (RF), 8
- Rayleigh
 - mode, 52
 - wave, 55
- Rayleigh–Ritz method
 - actuator, 73
 - microdiaphragm, 94
- Rayleigh-Ritz, 174
- Reynolds number, 11, 40, 128
- rotation of axes
 - X-convention, 58
 - Bond–Transformation, 58
- SAW time period, 64
- standard imaginary unit, 57
- static analysis
 - actuator, 76
 - microdiaphragm, 106
- stiffness tensor, 56
- surface acoustic wave, 8, 14, 33, 40, 50
 - accelerometer, 41
 - gyroscoope, 41
 - SAW applications, 41
 - SAW correlator, 8, 42, 87
 - SAW device, 8, 13, 40, 51, 87
 - SAW frequency, 45
- Tesla valve, 39, 40
- transcutaneous systems, 177
- transient analysis
 - actuator, 78
 - micropump, 139
- trigger frequency, 45
- viscosity, 142
- volume averages flow rate, 166
- volume–averaged velocity, 119
- Von Mises stress
 - actuator, 79
- wave vector, 57
- wavelength, 57
- wireless, 4

Résumé



Don Dissanayake graduated from Bachelor of Engineering (Computer Systems) with first class honours at The University of Adelaide in 2004. He then worked as an Electronic Design/ Production Engineer for Maptek Pty Ltd in Adelaide.

Don commenced his Ph.D in 2006 under the supervision of Dr. Said Al-Sarawi (School of Electrical and Electronic Engineering), Prof. Derek Abbott (School of Electrical and Electronic Engineering), and Dr. Tien-Fu Lu (School of Mechanical Engineering) at The University of Adelaide. He completed his Ph.D in 2009.

Don's research interests include micro-/nano- technology (Bio-MEMS, RF-MEMS, and NEMS), biomedical research, numerical modelling; including finite element modelling and analysis, and computational fluid dynamics. He received a full scholarship to commence his Ph.D, and also became a State Finalist at the *2009 AusBiotech-GST Student Excellence Awards*, in recognition of his achievements as an emerging researcher.

Don has authored over ten peer-reviewed publications, including two book chapters, and a journal article. He has given seven international conference presentations, and received the Best Presentation Award at the *3rd International Conference on Sensing Technology* in 2008. Don has also participated as a Technical Publications Reviewer for IEEE Sensors Journal (ISSN: 1530-437X) published by IEEE Sensors Council, and for Sensors Journal (ISSN 1424-8220; CODEN: SENSC9), published by Molecular Diversity Preservation International (MDPI).

Scientific Genealogy

Don Wenura Dissanayake's Scientific Genealogy

