

1064 nm injection mode-locked Nd:YAG laser
optimized for guide star applications

by

Thomas P. Rutten

Thesis submitted for the degree of
Doctor of Philosophy
in
the University of Adelaide
Department of Physics
December, 2009

Contents

1	Adaptive optics systems for astronomy	1
1.1	Introduction	1
1.2	Conventional single-conjugate adaptive optics systems	3
1.3	Artificial guide stars	5
1.3.1	Rayleigh guide stars	5
1.3.2	Sodium guide stars	6
1.4	Adaptive optics systems for future large-aperture observatories	8
1.4.1	Multiple beacons for atmospheric tomography	8
1.4.2	Gemini guide star requirements for MCAO on ELTs	8
1.5	This thesis	12
2	Injection mode-locked guide star laser design	15
2.1	Introduction	15
2.2	Guide star system design overview	15
2.3	Injection mode-locking	17
2.3.1	Objective	17
2.3.2	Mode-locking of laser resonators	17
2.3.3	Injection mode-locking	19
2.3.4	Conclusion	24
2.4	Slave resonator design	24
2.4.1	Introduction	24
2.4.2	Travelling wave ring resonator design	24
2.4.3	Conclusion	26
2.5	High power sum frequency generation	27
2.5.1	Introduction	27
2.5.2	Theory of SFG	28
2.5.3	Evaluation of common SFG materials	29
2.5.4	Estimation of SFG conversion efficiency for LBO	31

2.6	Power scaling	34
2.6.1	Design options	34
2.6.2	Master oscillator power amplifiers	35
2.7	Comments 1319 nm lasers	35
2.8	Frequency locking to the sodium line	36
2.9	Conclusions	38
3	Design verification experiments using a subscale, 1064 nm Nd:YAG laser	39
3.1	Objective	39
3.2	Laser head	40
3.3	Slave resonator design details	41
3.3.1	Resonator stability	43
3.3.2	Intra-cavity telescopes	45
3.4	Seed pulse generator	46
3.5	Q-switch driver	47
3.6	Injection mode-locked slave laser performance	50
3.6.1	Aligning the ring oscillator	50
3.6.2	Pulse energy	50
3.6.3	Micro-pulse jitter	51
3.6.4	Bandwidth control	52
3.7	Discussion and conclusions	56
4	Q-switched pulse stretching	59
4.1	Introduction	59
4.2	Experimental set-up	60
4.3	Numerical modelling of pulse stretching	62
4.4	Q-switch driver	68
4.5	Results	69
4.6	Discussion and conclusions	72
5	High power laser head design choice	73
5.1	Background	73
5.2	Objective	73
5.3	Laser head requirements	74
5.4	Thermal effects in high power lasers	74
5.4.1	Thermal lensing	75

5.4.2	Thermal stress and thermal birefringence	75
5.5	Rod lasers	76
5.6	Slab lasers	77
5.7	Design choice	79
5.8	Conclusions	80
6	Design and construction of the high power laser head	81
6.1	Introduction	81
6.2	Design summary	82
6.3	Laser slab design	83
6.3.1	Slab height	83
6.3.2	Slab width	87
6.3.3	Slab length	92
6.3.4	Parasitic oscillation control	92
6.4	Laser head construction	92
6.4.1	Laser pump modules	92
6.4.2	Teflon coating	96
6.5	Conclusions	99
7	Performance of the high power 1064 nm laser	101
7.1	Introduction	101
7.2	Pump laser performance	102
7.2.1	QCW laser diode arrays	102
7.2.2	Laser diode drivers	102
7.2.3	Water cooling system	103
7.2.4	Interlock system	105
7.2.5	Performance of individual laser diode arrays	105
7.2.6	Total pump power and absorbed pump power	106
7.3	Multi-mode performance of the high power laser head	108
7.3.1	The Mach-Zender interferometer	109
7.3.2	Measurement of thermal focal power using a tilted wavefront	113
7.4	Injection mode-locked laser performance	115
7.4.1	Resonator design	115
7.4.2	Injection mode-locked laser power at 800 Hz PRF	117
7.4.3	Reproducibility of slab mounting	117
7.4.4	Q-switched pulse stretching	119
7.4.5	Beam quality measurement	120

7.4.6	Laser bandwidth measurements	122
7.5	Conclusions	124
8	Conclusions	129
A	Publications	133
B	Zero jitter picosecond delay generator	157
C	High voltage high bandwidth attenuator	159
D	Pulse stretching model parameters	163
E	Laser slab and waveguide schematic diagrams	165

Abstract

In recent years, the emergence of powerful, sodium-resonant laser sources has led to a dramatic improvement in resolution at many of the world's large aperture observatories. The lasers are used to create artificial beacons (or guide stars) by fluorescing atmospheric sodium. Light from the beacon, returning from altitude, probes the intervening turbulence and the phase distortions detected are subsequently corrected using adaptive optics. Near-diffraction limited imaging has now been achieved on observatories with diameters up to 8 m using this technique. Future 30-100 m diameter telescopes will require new laser sources having higher average powers and innovative pulse formats to implement new forms of atmospheric tomography and correction. In this thesis I present the design and development of a new laser system for this purpose.

The laser design that I describe uses sum frequency generation (SFG) of 1064 nm and 1319 nm Nd:YAG lasers to produce the sodium wavelength, and introduces the novel application of injection mode-locking as a robust method to control the lasers wavelength and bandwidth. The high peak power and low timing jitter of the mode-locked (micro) pulses allows for efficient SFG of the 1064 and 1319 nm beams. Each slave laser is Q-switched and the duration of the Q-switched (macro) pulses are optimised to reduce star elongation and bleaching of the sodium.

The experimental work presented in this thesis is focused on the realization of a 1064 nm injection mode-locked slave laser, whose performance is optimised for use in the SFG guide star system. The work can be roughly divided into two sections. Firstly, results are presented from a low average power proof of principle laser which was used for risk reduction experiments, then secondly, a higher average power laser using a new laser head design is presented.

With the proof of concept laser it is shown that the injection mode-locking technique is robust and can be used to generate an ideal pulse burst with both wavelength and bandwidth control. A new method of Q-switched pulse stretching was implemented and the results show that the Q-switched pulses can be extended by a factor of 4.5 without a reduction in pulse energy.

The later part of the experimental work consists of a description of the design, construction and testing of a new high average power laser head used to generate the power levels required for the final guide star system. The laser head uses a zigzag Nd:YAG slab, pumped from each side by high average power laser diode arrays. This laser is shown to be capable of generating one of the highest average powers reported in the literature for an electro-optically Q-switched, diffraction limited Nd:YAG laser in a stable cavity.

This work contains no material which has been accepted for the award of any other degree or diploma in any university or other tertiary institution to Thomas Rutten and, to the best of my knowledge and belief, contains no material previously published or written by another person, except where due reference has been made in the text.

I give consent to this copy of my thesis when deposited in the University Library, being made available for loan and photocopying, subject to the provisions of the Copyright Act 1968. The author acknowledges that copyright of published works contained within this thesis (as listed below) resides with the copyright holder(s) of those works.

I also give permission for the digital version of my thesis to be made available on the web, via the Universitys digital research repository, the Library catalogue, the Australasian Digital Theses Program (ADTP) and also through web search engines, unless permission has been granted by the University to restrict access for a period of time.

Publications resulting from this work:

- T. P. Rutten, P. J. Veitch, C. d’Orgeville and J. Munch, “Injection mode-locked guide star laser concept and design verification experiments,” *Opt. Express* vol. 15 (5), pp. 2369-2374 Mar. 2007.
- T. P. Rutten, N. Wild and P. J. Veitch, “Fast rise time, long pulse width, kilohertz repetition rate Q-switch driver,” *Rev. Sci. Instrum.* vol. 78, 073108 Jun. 2007.
- T. P. Rutten, P. J. Veitch and J. Munch, “Efficient pulse stretching of Q-switched lasers,” *IEEE J. Quantum Electron.* vol. 44 (10), pp. 911-915 Oct. 2008.
- J. Munch, T. P. Rutten, N. Simakov, M. Hamilton, C. d’Orgeville and P. Veitch, “A new guide star laser using optimized injection mode-locking,” *Proc. SPIE*, vol. 7015, June 2008

SIGNED:

DATE:

Supervisors: Prof. J. Munch and A/Prof. P. Veitch

Acknowledgments

It is a tough road to travel when undertaking a PhD. When I first started, I stood back and observed what seemed to be an impenetrable wilderness, with tangled undergrowth and dangerous creatures lurking within. My supervisors, Jesper and Peter were the first to show me where I had to go. They pointed to a region far on the horizon and, with promises of great rewards and adventure, they showed me the direction in which to travel and set me upon the road to completion. Thank you Jesper and Peter for your guidance and support, without your help I would surely have been lost along the way.

To my colleagues in the optics group: Alex H, Alex D, Damian M, David H, Francois, Keiron, Nikita, Miftar, Nick, Sean, Shu, Aidan, Mathew and Ka, you provided so much helpful advice, thank you for your assistance and for providing a place to rest where I could forget about work and relax.

Damien, Murray and Dave O., we had many helpful discussions and you contributed a great deal to the solution of many important problems I faced.

I would also like to thank all the technical staff who provided assistance with this project. Neville, I am deeply indebted to you for being so generous with your time and for having the patience to teach me. To Blair and Trevor, your assistance in the workshop was essential and without your assistance I could not have progressed. I also thank the two Bobs and Peter A. for the excellent contributions and advice you gave.

To Eva and my colleagues at the RAH, your encouragement and support while writing was greatly appreciated.

I would like to thank the Gemini Observatory for providing funding for this work and Northrop Grumman for the loan of vital hardware.

Lastly I would like to thank my Family and friends. You provided the personal support and encouragement I needed to stick to my goals and keep going when times were tough. Thank you.